

MAXXTEK Gigabit 10 Fiber Switch



ITEM	MMS-1810
Fixed Port	8*10/100/1000Base-TX RJ45 port (Data) 10*1000M SFP (Layer 2 Unmanaged Switch)
Network Protocol	IEEE802.3 IEEE802.3i 10BASE-T IEEE802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE802.3x IEEE 802.3z 1000BASE-X
Port Specification	10/100/1000BaseT (X) Auto
Transmission Mode	Store and Forward(full wirespeed)
Bandwidth	52Gbps
Packet Forwarding	40.32Mpps
MAC Address	8 K
Buffer	4.1M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter) Optional single mode single fiber(MAX 20KM) Optional single mode double fiber (MAX 20KM) Optional multiple mode double fiber(MAX 850M/2KM) Optional 3-80KM SFP
Watt	≤30W ;
LED Indicator	PWR:Power LED 1~16:(SFP LED) Port:(Green=10/100M LED+Orange=1000M LED)
Power	Built-in power AC 100~240V 50/60HZ 1A
Operating Temperature/Humidity	-10~+55°C ; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C ; 5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	440mm*205mm*45mm 515mm*295mm*95mm
N.W/G.W (kg)	2.2kg/3.1kg
Installation	Rack-mount(optional machine hanger spare parts)
Lightning Protection level	3KV 8/20us ; IP30
Warranty	1 Year

Note: SFP Module supported (as per requirements)